Your comfort. Every season.

LUMA dehumidifiers

MANUFACTURER DOCUMENT / DOCUMENT FABRICANT

The following 2 pages reproduce the manufacturer document unchanged.
Les 2 pages suivantes reproduisent le document fabricant sans modification.
This Canada cover is editorial. Specifications retain their original source.
Cette couverture est éditoriale. Les données conservent leur source originale.

Questions about your project? / Un projet à préparer?

info@vinotech.ca | 1 844 660-5482

VINO
CANADA

Smart Home Dehumidifier

35 Pints & 50 Pints

Auto Mode / Sleep Mode
Continuous Mode / Set Mode

Auto-Defrosting Function

Operating Temp.
41°F ~ 90°F

Timer Function
No Wifi: 1-12H
Wifi: 1-24H

APP
Smart Control

FUNCTIONS

VINO Smart Home Dehumidifier

ECO
Auto Mode
Sleep Mode
Continuous Mode
Set Mode
Auto Defrosting
Timer
Hidden Display

Low Noise
Child Lock
Continuous Drainage
Universal Wheel
Self-Diagnosis
WIFI (Optional)
APP Smart Control
Pump Optional

PRODUCT

Front



Back

Side

Control Panel

SPECIFICATIONS

Parameter	Unit	35 Pints		50 Pints	
		Non drain pump	With drain pump	Non drain pump	With drain pump
Model	--	VD35G-FD3A	VD35G-FD3B	VD50K-FD3A	VD50K-FD3B
Power Supply	Vac/Hz/Ph	115-60-1	115-60-1	115-60-1	115-60-1
Dehumidifying Volume (65°F/60%RH)	Pints/D	36.53	36.53	50	50
Dehumidifying Volume (80°F/60%RH)	Pints/D	48	48	65	65
Dehumidifying Volume (86°F/80%RH)	Pints/D	74	74	110	110
Rated Input	W	670	670	950	950
Rated Current	A	5.9	5.9	8.5	8.5
Circular Air Volume Airflow	CFM	156(High) / 123(low)	156(High / 123(low)	223(High) / 161(low)	223(High) / 161(low)
Sound Pressure Level	dB (A)	43 ~ 45	43 ~ 45	44 ~ 47	44 ~ 47
Set Humidity Range	--	30% ~ 80%	30% ~ 80%	30% ~ 80%	30% ~ 80%
Operation Temp.(Ambient Temp.)	°F	41 ~ 90 (5 ~ 32 °C)	41 ~ 90 (5 ~ 32 °C)	41 ~ 90 (5 ~ 32 °C)	41 ~ 90 (5 ~ 32 °C)
Refrigerant	--	R32	R32	R32	R32
Net Weight	lb	34.4	35.3	42.98	43.87
Dimension (W×H×D)	inch	14-6/8 x 19-21/32 x 9-	14-6/8 x 19-21/32 x 9-	15-5/32 x 23-5/8 x 9-1/2	15-5/32 x 23-5/8 x 9-1/2
Loading Quantity (20'/40'/40'HQ)	--	344 / 704 / 875	344 / 704 / 875	297 / 603 / 804	297 / 603 / 804